

Item code: 70335-SICH-20125PR

Product description: Speed DOME camera VALUE Series

Main features: 2 MP IR Network Speed Dome, 3D-DNR, BLC, HLC, Defog, EIS, Colour: 0.005 Lux/(F1.6, AGC ON), B/W: 0.001 Lux/(F1.6, AGC ON), 0 Lux with IR, IP66, Power adapter included. With the 25X optical zoom lens, the camera offers more details over expansive areas.



SPECIFICATIONS

Camera Module	
Image Sensor	1/2.8" progressive scan CMOS
Min. Illumination	Colour: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR
White Balance	Auto/Manual/ATW (Auto-tracking White Balance)/Indoor/Outdoor/Fluorescent Lamp/Sodium Lamp
Gain	Auto/Manual
Shutter Time	50 Hz: 1/1 ÷ 1/30,000 s 60 Hz: 1/1 ÷ 1/30,000 s
Day & Night	IR Cut Filter
Digital Zoom	16X
Privacy Mask	24 programmable privacy masks, mask colour configurable
Focus Mode	Auto/Semi-automatic/Manual
WDR	120 dB WDR
Lens	
Focal Length	4.8 ÷ 120 mm, 25X optical zoom
Zoom Speed	~3.6 s (optical lens, wide-tele)
Field of View	Horizontal FOV: 57.6° ÷ 2.5° (Wide-Tele) Vertical FOV: 34.4° ÷ 1.4° (Wide-Tele) Diagonal FOV : 64.5° ÷ 2.9° (Wide-Tele)
Working Distance	10 ÷ 1,500 mm (wide-tele)
Aperture Range	F1.6 ÷ F3.5
IR	
IR Distance	150 m
Smart IR	Yes
PTZ	
Movement Range (Pan)	360° endless
Pan Speed	Configurable, from 0.1°/s to 120°/s Preset speed: 120°/s
Movement Range (Tilt)	From -15° ÷ 90° (auto-flip)
Tilt Speed	Configurable, from 0.1°/s to 80°/s Preset Speed: 80°/s



BS OHSAS 18001: 2007
Occupational Health and
Safety Management System



ISO 9001: 2015
Quality Management
System



ISO 14001: 2015
Environmental Management
System



CI ITPI: 2015
100% Made in Italy
Certificate



MAZi – Brand distributed by LINCE ITALIA S.p.A.
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
 Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 1 di 3

Proportional Zoom	Yes
Presets	300
Patrol Scan	8 patrols, up to 32 presets for each patrol
Pattern Scan	4 pattern scans, record time over 10 minutes for each scan
Power-off Memory	Yes
Park Action	Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan
3D Positioning	Yes
PTZ Position Display	Yes
Preset Freezing	Yes
Scheduled Task	Preset/Pattern Scan/Patrol Scan/Auto Scan/Tilt Scan/Random Scan/Frame Scan/Panorama Scan/Dome Reboot/Dome Adjust/Aux Output
Compression Standard	
Video Compression	<i>Main Stream:</i> H.265+/H.265/H.264+/H.264 <i>Sub-stream:</i> H.265/H.264/MJPEG <i>Third Stream:</i> H.265/H.264/MJPEG
H.264 Type	Baseline Profile/Main Profile/High Profile
H.264+	Yes
H.265 Type	Baseline Profile/Main Profile/High Profile
H.265+	Yes
Video Bitrate	32 ÷ 16,384 Kbps
Audio Compression	G.711alaw/G.711ulaw/G.722.1/G.726/MP2L2/PCM
Audio Bitrate	G.711alaw/G.711ulaw: 64 Kbps G.722.1/G.726: 16 Kbps MP212/PCM: 32 ÷ 160 Kbps
SVC	Yes
Smart Features	
Basic Event	Motion Detection, Video Tampering Detection, Exception
Smart Event	Intrusion Detection, Line Crossing Detection, Region Entrance Detection, Region Exiting Detection, Object Removal Detection, Unattended Baggage Detection, Audio Exception Detection
Smart Record	ANR (Automatic Network Replenishment), Dual-VCA
ROI	Main stream, sub-stream, and third stream respectively support four fixed areas.
Image	
Max. Resolution	1920 × 1080
Main Stream	50 Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720) 50fps (1280 × 960, 1280 × 720) 60 Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720) 60fps (1280 × 960, 1280 × 720)
Sub-Stream	50 Hz: 25fps (704 × 576, 640 × 480, 352 × 288) 60 Hz: 30fps (704 × 480, 640 × 480, 352 × 240)
Third Stream	50 Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288)

	60 Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)
Image Enhancement	HLC/BLC/3D DNR/Defog/EIS/Regional Exposure/Regional Focus
Network	
Network Storage	Built-in memory card slot, support Micro SD/SDHC/SDXC, up to 256 GB; NAS (NFS, SMB/ CIFS), ANR
Alarm Linkage	Alarm actions, such as Preset, Patrol Scan, Pattern Scan, Trigger Recording, Trigger Alarm Output, Notify Surveillance Center, Upload to FTP/Memory Card/NAS, Send Email, etc.
Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
API	ONVIF (Profile S, Profile G, Profile T), ISAPI, SDK
Simultaneous Live View	Up to 20 channels
User/Host	Up to 32 users 3 levels: Administrator, Operator and User
Security Measures	User authentication (ID and PW), Host authentication (MAC address); HTTPS encryption; IEEE 802.1x port-based network access control; IP address filtering
Client	Guarding Vision (CTR-MAZi), CMS-MAZi
Web Browser	IE 8 to 11, Chrome 31.0+, Firefox 30.0+, Edge 16.16299+
Interface	
Network Interface	1 RJ45 10 M/100 M Ethernet, Hi-PoE
Audio	1-ch audio input, 2 to 2.4 V[p-p], 1 K Ω $\pm$ 10% 1-ch audio output, line level, impedance: 600 Ω
Alarm	2-ch alarm input/1-ch alarm output
General	
Language (Web Browser Access)	32 languages: English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil)
Power	24 VAac 2.2 A, 50/60 Hz and Hi-PoE, 42.5 $\div$ 57 Vdc, 1.41 A Max. 30 W, including Max. 10 W for IR
Working Temperature	-30 $^{\circ}$ C $\div$ 65 $^{\circ}$ C (-22 $^{\circ}$ F $\div$ 149 $^{\circ}$ F)
Working Humidity	$\leq$ 90%
Protection Level	IP66 Standard, 4000 V Lightning Protection, Surge Protection and Voltage Transient Protection
Material	ADC 12, PC, PC+10% GF
Dimensions	Φ 208 × 345 mm (Φ 8.19 × 13.58 inch)
Weight	~3.3 kg (7.28 lb)

DORI

The DORI (*Detect, Observe, Recognize, Identify*) distance gives the general idea of the camera ability to distinguish persons or objects within its field of view. It is calculated based on the camera sensor specification and the criteria given by EN 62676-4: 2015.

DORI	Detect	Observe	Recognize	Identify
Definition	25 px/m	63 px/m	125 px/m	250 px/m
Distance (Tele)	1600.0 m (5249.3 ft)	634.9 m (2083.1 ft)	320.0 m (1049.9 ft)	160.0 m (524.9 ft)



BS OHSAS 18001: 2007
Occupational Health and Safety Management System

ISO 14001: 2015
Environmental Management System



ISO 9001: 2015
Quality Management System



CI ITPI: 2015
100% Made in Italy Certificate



MAZi – Brand distributed by LINCE ITALIA S.p.A.
Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net - info@lince.net
MD-03.11 Rev. 6 - Pag.: 3 di 3