



IVN-21EVR

IP Turret Camera 2MP, 1080P, 2.8-12mm lens, 3pcs array IR, POE, Hardrest, audio I/O, waterproof RJ45

High performance CMOS image sensor, with 2MP resolution

H.264/H.265/H.265+, dual-stream

Resolution 1920*1080

Onvif

ICR switching

IP66 metal case, 2.8-12mm lens

3pcs Array IR, Max, 30M

IP66 metal Turret case

Power supply: PoE/DC12V 500mA

1CH AUDIO I/O, Support hardware reset

Camera

Image Sensor 1/2.9, 2MP CMOS GC2063

Min. Illumination Colour 0.01 Lux

Signal to noise ratio ≥ 37 dB

Video

Video processing

Supports automatic white balance, supports 3-DNR, dWDR, anti-face overexposure, and dehazing function, H.264/H.265/H.265+ different encoding formats are available, realize ultra-low storage, adjustable bit rate/frame rate

Audio

Audio Port One audio input One audio output, G711U/G711A encoding, support simplex two-way voice intercom

Network

Network Interface One RJ45, 10/100M adaptive Ethernet interface 2KV lightning protection

Protocol Support Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, optional GB28181, RTMP and multiple private NVR protocols IE6.0 and above (Web Server embedded in the device) browser use Motion detection and OSD customization

Intelligent Functions P2P cloud service Support mobile web access Support IP filtering

Image

Image Resolution *Main stream:* 1080P(default)/720P/D1@30fps
Sub stream: D1/VGA/640*360/CIF@30fps

General

Mobile client Support Windows Mobile, iPhone, iPad, Android

Business functions Support IE6.0 and above (device embedded Web Server) browser browsing, support front-end storage playback/download, support unified client software, Support CMS platform system application, provide SDK development kit

Work Environment $-30^{\circ}\text{C} \div \sim 85^{\circ}\text{C}$

Camera Dimension 145 (D) x 107.86 (H) mm