



IVN-23EIR

IP Turret Camera, 2MP, 2.8 mm lens, 2pcs Array IR Led, 20M, PoE and DC12V 400mA

High performance CMOS image sensor, with 2MP resolution
H.264/H.265/H.265+ dual-stream
Max resolution 2304*1296
Onvif
ICR switching
IP66 Metal case
2PCS Array IR Led, 20M
2.8 mm lens
PoE and DC12V 400 mA

Camera

Image Sensor	1/2.8, SONY SENSOR IMX307
Min. Illumination	Colour 0.01 Lux
Signal to noise ratio	≥ 50 dB

Video

Video processing	Supports automatic white balance, supports 3DNR,WDR,Support anti-overexposure of face, support defogging function , H.264/H.265/H.265+ different encoding formats are available, realize ultra-low storage, adjustable bit rate/frame rate
------------------	---

Audio

Audio Port	Not make audio I/O
------------	--------------------

Network

Network Interface	One RJ45, 10/100M adaptive Ethernet interface 2KV lightning protection meter
Protocol Support	Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, optional GB28181, RTMP and multiple private NVR protocols IE6.0 and above (Web Server embedded in the device) browser use Motion detection and OSD customization
Intelligent Functions	Humanoid detection P2P cloud service Support mobile web access Support IP filtering

Image

Image Resolution	<i>Main stream:</i> 3MP@25fps,1080P (default)/720P/D1@30fps <i>Sub stream:</i> D1/VGA/640*360/CIF@30fps
------------------	--

General

Mobile client	Support Windows Mobile, iPhone, iPad, Android
Business functions	Support IE6.0 and above (device embedded Web Server) browser browsing, support front-end storage playback/download, support unified client software, Support CMS platform system application, provide SDK development kit
Work Environment	-30 °C ÷ ~85 °C
Camera Dimension	106.61 (D) x 81.78 (H) mm