

Item code: 70281-IWH-42LIX

Product description: IP BULLET Camera VALUE Series 4 MP

Main features: 4 MP IR Fixed Bullet Network Camera, Colour: 0.01 Lux/(F 1.2, AGC ON), 0 Lux with IR, 3 streams, 3D-DNR, ICR, EXIR 2.0, Built-in micro SD/SDHC/SDXC slot, IP67, Line crossing detection, Intrusion detection, Face detection.


SPECIFICATIONS

Camera	
Image sensor	1/3" progressive scan CMOS
Minimum Illumination	Colour: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Yes
Day & Night	IR cut filter
Digital Noise Reduction	3D-DNR
WDR	120 dB
3-Axis Adjustment	Pan: 0° ÷ 360°; Tilt: 0° ÷ 90°; Rotate: 0° ÷ 360°
Lens	
Focal Length	2.8 mm
Aperture	F1.6
Focus	Fixed
FOV	horizontal FOV 103° vertical FOV 58° diagonal FOV 123°
Lens Mount	M12
IR	
IR Range	Up to 30 m
Wavelength	850 nm
Compression Standard	
Video compression	<i>Main stream:</i> H.265/H.264 <i>Sub-stream:</i> H.265/H.264/MJPEG <i>Third stream:</i> H.265/H.264
H.264 Type	Main Profile/High Profile
H.264+	Main stream supports
H.265 Type	Main Profile
H.265+	Main stream support
Video Bit Rate	32 Kbps to 16 Mbps
Smart Feature-set	
Smart Event	Line crossing detection, intrusion detection, face detection
Basic Event	Motion detection, video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error)
Linkage Method	<i>Trigger recording:</i> memory card, network storage, pre-record and post-record


BS OHSAS 18001: 2007
 Occupational Health and
 Safety Management System

ISO 9001: 2015
 Quality Management
 System

ISO 14001: 2015
 Environmental Management
 System

CI ITPI: 2015
 100% Made in Italy
 Certificate


MAZi – Brand distributed by LINCe ITALIA S.p.A.
 Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
 Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 1 di 3

	Trigger captured pictures uploading: FTP, HTTP, NAS, Email Trigger notification: HTTP, ISAPI, alarm output, Email
Region of Interest	1 fixed region for main stream and sub-stream
Image	
Max. Resolution	2688 × 1520
Main Stream	50 Hz: 25fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080, 1280 × 720) 60 Hz: 30fps (2688 × 1520, 2560 × 1440, 2304 × 1296, 1920 × 1080, 1280 × 720)
Sub-stream	50 Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60 Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
Third Stream	50 Hz: 25fps (1280 × 720, 640 × 360, 352 × 288) 60 Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)
Image Enhancement	BLC, 3D-DNR, HLC
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness, AGC, and white balance adjustable by client software or web browser
Target Cropping	No
Day/Night Switch	Day/Night/Auto/Schedule
Network	
Network Storage	Support Micro SD/SDHC/SDXC card (128 G), local storage and NAS (NFS,SMB/CIFS), ANR
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS
General Function	Anti-flicker, three streams, heartbeat, mirror, privacy masks, password reset via e-mail, pixel counter, HTTP listening
API	ONVIF (PROFILE S, PROFILE G, PROFILE T), ISAPI, SDK
Security	Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS 1.2, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for ONVIF, TLS1.2
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users 3 levels: Administrator, Operator and User
Client	CMS-MAZi, Guarding Vision
Web Browser	Plug-in required live view: IE8+ Plug-in free live view: Chrome 57.0+, Firefox 52.0+, Safari 11+ Local Service: Chrome 41.0+, Firefox 30.0+
Interface	
Communication Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
Video output	No
On-board storage	Built-in Micro SD/SDHC/SDXC slot, up to 128 GB
SVC	H.264 and H.265 encoding
Reset Button	Yes
General	
Operating Conditions	-30 °C + +60 °C (-22 °F + +140 °F); humidity 95% or less (non-condensing)
Web Client Language	32 languages English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil)
Power Supply	12 Vdc ± 25%, Ø 5.5 mm coaxial power plug PoE (802.3af, class 3)



Power Consumption and Current	DC: 12 V, 0.5 A, max. 6 W PoE: (802.3af, 36 ÷ 57 V), 0.2 A ÷ 0.1 A, max 7.5 W
Protection Level	IP67
Material	Metal
Dimensions	<i>Camera:</i> Φ 70 × 155.03 mm (Φ 2.8" × 6.1") <i>Package:</i> 216 × 121 × 118 mm (8.5" × 4.8" × 4.7")
Weight	<i>Camera:</i> ~420 g (0.9 lb) <i>With package:</i> ~700 g (1.5 lb)

**BS OHSAS 18001: 2007**
Occupational Health and
Safety Management System**ISO 9001: 2015**
Quality Management
System**ISO 14001: 2015**
Environmental Management
System**CI ITPI: 2015**
100% Made in Italy
Certificate

MAZi – Brand distributed by LINCE ITALIA S.p.A.
Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 3 di 3