

Item code: 70309-TDH-52LAX

Product description: HD-TVI DOME Camera VALUE Series

Main features: 5 MP-20 fps, 4 MP-25 fps (P)/30 fps (N) (Default), EXIR, ICR,
 Colour: 0.01 Lux/F 1.2, DNR, IP67.



SPECIFICATIONS

Camera	
Image Sensor	5 MP CMOS
Resolution	2560 (H) × 1944 (V)
Frame Rate	PAL: 5 M@20fps, 4 M@25fps, 1080p@25fps NTSC: 5 M@20fps, 4 M@30fps, 1080p@30fps
Min. illumination	Colour: 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 ÷ 1/50,000 s NTSC: 1/30 ÷ 1/50,000 s
Lens	2.7 ÷ 13.5 mm motorized varifocal lens
Horizontal Field of View	95.7° ÷ 29.1°
Lens Mount	Φ14
Day & Night	IR cut filter
Synchronization	Internal synchronization
Angle Adjustment	Pan: 0° ÷ 355° Tilt: 0° ÷ 75° Rotation: 0° ÷ 355°
Menu	
AGC	Support
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	ATW/MWB
BLC	Support
DWDR (Digital Wide Dynamic Range)	Support
Function	Brightness, Sharpness, Mirror, Smart IR
Interface	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40 °C ÷ 60 °C (-40 °F ÷ 140 °F); humidity: 90% or less (non-condensation)
Power Supply	12 Vdc ± 15%; 24 Vac ± 15%
Power Consumption	Max 4.4 W

Protection Level	IP67, IK10
Material	Metal
IR Range	Up to 40 m
Dimensions	Φ 145 × 111.3 mm (Φ 5.70" × 4.37")
Weight	~815 g (1.80 lb)



BS OHSAS 18001: 2007
Occupational Health and
Safety Management System



ISO 9001: 2015
Quality Management
System



ISO 14001: 2015
Environmental Management
System



CI ITPI: 2015
100% Made in Italy
Certificate



MAZi – Brand distributed by LINCe ITALIA S.p.A.
Via Variante di Cancelliera s.n.c., 00072 Ariccia (RM) Italia
Tel.: +39 06 92928252 - Fax: +39 06 92942586
www.lince.net – info@lince.net
MD-03.11 Rev. 6 - Pag.: 2 di 2