



## IVN-22EIR

IP Turret Camera, 3.6mm lens, 2MP, 2pcs array IR

High performance CMOS image sensor, with 2 MP resolution  
H.264/H.265/H.265+ dual-stream  
Max resolution 1920\*1080  
Onvif  
ICR switching  
Metal Turret case  
18PCS SMD IR Led, 20M  
3.6 mm lens  
DC12V 350 mA

| Camera                |                                                                                                                                                                                                                               |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Image Sensor          | 1/2.9, 2 MP CMOS GC2063                                                                                                                                                                                                       |
| Min. Illumination     | Colour 0.01 Lux                                                                                                                                                                                                               |
| Signal to noise ratio | ≥ 37 dB                                                                                                                                                                                                                       |
| Video                 |                                                                                                                                                                                                                               |
| Video processing      | Supports automatic white balance, supports 3-DNR, dWDR, anti-face overexposure, and dehazing function, H.264/H.265/H.265+ different encoding formats are available, realize ultra-low storage, adjustable bit rate/frame rate |
| Audio                 |                                                                                                                                                                                                                               |
| Audio Port            | One audio input One audio output, G711U/G711A encoding, support simplex two-way voice intercom                                                                                                                                |
| Network               |                                                                                                                                                                                                                               |
| Network Interface     | One RJ45, 10/100M adaptive Ethernet interface 2KV lightning protection                                                                                                                                                        |
| Protocol Support      | Support HTTP/RTSP/NTP/DHCP/ONVIF/P2P lamp network protocol, optional GB28181, RTMP and multiple private NVR protocols                                                                                                         |
| Intelligent Functions | IE6.0 and above (Web Server embedded in the device) browser use Motion detection and OSD customization<br>P2P cloud service<br>Support mobile web access<br>Support IP filtering                                              |
| Image                 |                                                                                                                                                                                                                               |
| Image Resolution      | <i>Main stream:</i><br>1080P(default)/720P/D1@30fps<br><i>Sub stream:</i><br>D1/VGA/640*360/CIF@30fps                                                                                                                         |
| General               |                                                                                                                                                                                                                               |
| Mobile client         | Support Windows Mobile, iPhone, iPad, Android                                                                                                                                                                                 |
| Business functions    | Support IE6.0 and above (device embedded Web Server) browser browsing, support front-end storage playback/download, support unified client software, Support CMS platform system application, provide SDK development kit     |
| Work Environment      | -30 °C ÷ ~85 °C                                                                                                                                                                                                               |
| Camera Dimension      | 106 (D) x 74 (H) mm                                                                                                                                                                                                           |