



ICE-21EIR

2 MP Fixed Cube Network Camera, 4 mm, 10 m IR, Wi-Fi, plastic.

1920 × 1080

Powerful Infrared LED lights; IR range: up to 10 m

H.264 dWDR

Support MicroSD card slot, up to 256 GB

3D-DNR Wi-Fi

\sim	$\overline{}$	m	\sim	ra
	а		ы	

Image Sensor 1/3" Progressive Scan CMOS

Shutter Speed Self-adaptive shutter

Day & Night IR-cut filter with auto-switching

DNR 3D-DNR WDR dWDR

Lens

Focal Length 4 mm

Aperture F2.4

FOV Horizontal: 75°; Vertical: 45°; Diagonal: 85°

Lens Mount M12

Image

Video Compression 1920 x 1080

Video Bit Rate Max: 15 fps; Self-Adaptive during network transmission

Compression

Max. Resolution H.264

Frame Rate Full HD, HD, Standard. Adaptive bit rate

Network

Smart Alarm Motion detection

Wi-Fi Pairing AP pairing

Wi-Fi

Standard IEEE802.11b/g/n

Security 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

Frequency Range 2.4 ~ 2.4835 GHz Channel Bandwidth Supports 20 MHz

Transmission Rate 11b: 11 Mbps; 11g: 54 Mbps; 11n: 72 Mbps

Interface

Storage MicroSD card slot (Max. 256 GB)

Power Micro USB

Wired Network 1 RJ45 (10/100 M self-adaptive Ethernet port)

Genera

Power Supply 5 Vdc, 1 A
Power Consumption 5 W Max
IR Range Up to 10 m

Operating Conditions $-10 \, ^{\circ}\text{C} \div 45 \, ^{\circ}\text{C} (14 \, ^{\circ}\text{F} \div 113 \, ^{\circ}\text{F}); \text{ humidity: } 95\% \text{ or less (non-condensing)}$

DS334 | Rev00 Mazi Security Systems





Dimensions	88 x 88 x 118.7 mm (3.46" x 3.46" x 4.67")
Packaging Dimensions	103 x 103 x 186 mm (4.06" x 4.06" x 7.32")
A1 . A4/ 1 1 .	250 = (0.44 ==)

Net Weight 259 g (9.14 oz)

Α	n	n	m	\cap	v	9
\neg	ν	ν		u		a

Certificates FCC/UL/CE/WEEE/REACH/RoHS

DS334 | Rev00 Mazi Security Systems



